(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



26 OCT 2004

(43) International Publication Date 27 November 2003 (27.11.2003)

PCT

(10) International Publication Number WO 03/097745 A1

(51) International Patent Classification7: 101/10, 69/00

(21) International Application Number: PCT/US03/15331

(22) International Filing Date: 15 May 2003 (15.05.2003)

(25) Filing Language:

English

C08L 83/04

(26) Publication Language:

English

(30) Priority Data: 60/381,654

16 May 2002 (16.05.2002) US

(71) Applicants (for all designated States except US): DOW CORNING CORPORATION [US/US]; 2200 West Salzburg Road, Midland, MI 48686-0994 (US). DOW CORNING TORAY SILICONE CO., LTD. [JP/JP]; 4th Floor, AIG Building, 1-1-3, Marunouchi, Chiyoda-ku, Tokyo 100-0005 (JP).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): ROMENESKO, David [US/US]; 4102 Elm Court, Midland, MI 48642 (US). SCHMIDT, Randall [US/US]; 813 Honeysuckle Circle, Midland, MI 48642 (US). TOGASHI, Atsushi [JP/JP]; 3-7-15-303 Nobuto, Cho-ku, Chiba-shi, Chiba Prefecture 260-0032 (JP). WIEBER, Gary [US/US]; 4407 Huron Drive, Midland, MI 48642 (US).
- (74) Common Representative: DOW CORNING COR-PORATION; TROY, Timothy, Patent Department . Mail CO1232, 2200 West Salzburg Road, Midland, MI 48686-0994 (US).
- AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, ning of each regular issue of the PCT Gazette.

GM, HR, HU, ID, II., IN, IS, JP, KE, KG, KP, KR, KZ, I.C. LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, II, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA. CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS. JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO palent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian pasent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES. FI, FR. GB, GR. HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ. GW. ML. MR. NE. SN. TD. TG)
- of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

(81) Designated States (national): AE, AG, AL, AM, AT, AU, For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the begin-

riangle (54) Title: FLAME RETARDANT COMPOSITIONS

(57) Abstract: This invention relates to a flame retardant composition comprising: (a) 81 to 99.99 weight percent of a thermoplastic resin, thermoset resin, thermoplastic resin blend, or thermoset resin blend which upon burning forms a char and (b) 0.01-19 weight percent of a silsesquioxane resin having a weight average molecular weight of greater than 300 and having the average molecular formula: (R2SiO10), (R2SiO20), (RSiO20), (SiO42)4 (RO10), (OH10), wherein each R is hydrogen, an alkyl group, an alkenyl group, or an aryl group having from 6 to 12 carbon atoms, a and b are zero or positive numbers and the value of a+b is greater than zero, c is a positive number, d, e and f are zero or positive numbers with the provisos that the copolymer comprises at least 40 mole percent of RsiO32 units, the copolymer comprises less than 10 mole percent SiO42 units, greater than 30 mole percent of the silicon-bonded R groups are silicon-bonded aryl groups, greater than 0.5 mole percent of the silicon-bonded R groups are silicon-bonded hydrogen atoms, the content of silicon-bonded hydroxyl groups is equal to or less than 2 weight percent, and the content of silicon-bonded alkoxy groups where the alkoxy group is methoxy or ethoxy is equal to or less than 5 weight percent.